

RELAY MODULES ONLY

15560.2

PRC 1/48V DC, Relay only 1PCO Gold plated

- Narrow 5 mm width
- Sensitice DC coil, 170 mW
- Secure isolation, VDE 0160/EN 50178
- 6 mm clearance and creepage distance
- Protection class II, VDE 0631/EN 60730



PRODUCT DESCRIPTION

TECHNICAL DATA

INPUT DATA

Coil voltage	48 V dc
Operating voltage	33,6-72 V dc
Holding voltage	0,4 Un dc
Release voltage	0,05 Un dc
Input power rating	0,217
Coil resistance	10600 Ω
Overvoltage category	III

OUTPUT DATA

Contact configuration	1 CO
Contact material	AgNi + Au
Rated V ac / switching V ac max	250 / 400 V ac
Switching capacity max	1500 VA
Contact load min	50 mW
Continuous current max / Inrush current max	6 / 10 A
Response / release time	12 / 5 ms
Bounce time at close of the NO/NC contact	3/8 ms

GENERAL DATA

Approvals	CE
Operating temperature from	-40 °C
Operating temperature to	85 °C
Electrical life in hours (AC1)	60x10 ³
Mechanical life hours	10x10 ⁶

DIMENSIONS & MATERIALS

Width	5 mm
Length	28 mm
Height	15 mm
Protection	RTIII (wash tight)

ADDITIONAL DATA

Tariff code	85364900
Country of origin	IT
Weight	5.2 g
Pack size	10