**OEM Automatic Ltd**
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# C16 INDUSTRIAL PCB MOUNT RELAY

C16A25PTL24D
Relay PCB 2-pole, 24 VDC




- 2 pole changeover contacts
- 7A switching current
- Din-rail mountable
- Available in AC and DC coil voltages

### PRODUCT DESCRIPTION

**The C16 relay range** is a PCB mount relay featuring **2 changeover contacts.**

Key features of the C16 range include:

- $AgSnO_2$ contact material
- 2 pole changeover contacts
- DIN-Rail Mountable
- Rated to switch up to 7A at 250VAC or 30VDC
- Coil Voltage Options: 12V, 24V, 48V, 110V, 230V (AC/DC variants available)
- 5mm grid

# TECHNICAL DATA

## INPUT DATA

| | |
|---|---|
| **Working Un** | 0,8 - 1,10 |
| **Coil voltage dc** | 24 V DC |

## OUTPUT DATA

| | |
|---|---|
| **Number of contacts** | 2 |
| **Contact material** | AgSnO2 |
| **Breaking capacity current** | 7 A |
| **Inrush max** | 15 A |

## GENERAL DATA

| | |
|---|---|
| **Width** | 13 mm |
| **Temperature operational min** | -55 °C |
| **Storage temperature min** | -55 °C |
| **Storage temperature max** | 70 °C |
| **Temperature operational max** | 70 °C |
| **Weight** | 17 g |

