OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

C16 INDUSTRIAL PCB MOUNT RELAY

C16A25PTL48D



- 2 pole changeover contacts
- 7A switching current
- Din-rail mountable
- Available in AC and DC coil voltages

PRODUCT DESCRIPTION

The C16 relay range is a PCB mount relay featuring **2 changeover contacts.**

Key features of the C16 range include:

- $AgSnO_2$ contact material
- 2 pole changeover contacts
- DIN-Rail Mountable
- Rated to switch up to 7A at 250VAC or 30VDC
- Coil Voltage Options: 12V, 24V, 48V, 110V, 230V (AC/DC variants available)
- 5mm grid

TECHNICAL DATA

INPUT DATA

Working Un	0,8 - 1,10
Coil voltage dc	48 V DC

OUTPUT DATA

Number of contacts	2
Contact material	AgSnO2
Breaking capacity current	7 A
Inrush max	15 A

GENERAL DATA

Width	13 mm
Temperature operational min	-55 °C
Storage temperature min	-55 °C
Storage temperature max	70 °C
Temperature operational max	70 °C
Weight	17 g

