OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

C18 PCB MOUNT RELAY

C18A15PT24A
Relay PCB 1-pole, 24 VAC



- 1 pole changeover contact
- Rated up to 10A or 16A
- 3.5mm or 5mm grid size
- Available in AC or DC coil voltages

PRODUCT DESCRIPTION

- $AgSnO_2$ contact material
- 1 pole changeover contacts
- Din-rail Mountable
- Rated to switch up to 10A at 250VAC or 30VDC. C18-B15PTL versions rated up to 16A.
- Coil Voltage Options: 12V, 24V, 48V, 110V, 230V (AC/DC variants available)
- 3.5 or 5mm grid

TECHNICAL DATA

INPUT DATA

Working Un	0,8 - 1,10
Coil voltage ac	24 V AC

OUTPUT DATA

Number of contacts	1
Contact material	AgSnO2
Breaking capacity current	10 A
Inrush max	25 A

GENERAL DATA

Width	13 mm
Temperature operational min	-55 °C
Storage temperature min	-55 °C
Storage temperature max	70 °C
Temperature operational max	70 °C
Weight	17 g

