

## C18 PCB MOUNT RELAY

C18A15PTL24A

- 1 pole changeover contact
- Rated up to 10A or 16A
- 3.5mm or 5mm grid size
- Available in AC or DC coil voltages



### PRODUCT DESCRIPTION

- AgSnO<sub>2</sub> contact material
- 1 pole changeover contacts
- Din-rail Mountable
- Rated to switch up to 10A at 250VAC or 30VDC. C18-B15PTL versions rated up to 16A.
- Coil Voltage Options: 12V, 24V, 48V, 110V, 230V (AC/DC variants available)
- 3.5 or 5mm grid

## TECHNICAL DATA

### INPUT DATA

|                 |            |
|-----------------|------------|
| Working Un      | 0,8 - 1,10 |
| Coil voltage ac | 24 V AC    |

### OUTPUT DATA

|                           |                    |
|---------------------------|--------------------|
| Number of contacts        | 1                  |
| Contact material          | AgSnO <sub>2</sub> |
| Breaking capacity current | 10 A               |
| Inrush max                | 25 A               |

GENERAL DATA

|                             |        |
|-----------------------------|--------|
| Width                       | 13 mm  |
| Temperature operational min | -55 °C |
| Storage temperature min     | -55 °C |
| Storage temperature max     | 70 °C  |
| Temperature operational max | 70 °C  |
| Weight                      | 17 g   |

