

C4 INDUSTRIAL RELAY

4-pole 10 A - MRC

C4-R3024A

Relay 14 Pin 3 Pole Latching 24V ac

- Marking system that can be custom-marked at factory
- Colour-coded test button, both lockable and spring-loaded
- Mechanical indication, double windows



PRODUCT DESCRIPTION

TECHNICAL DATA

INPUT DATA

Coil voltage ac	24 V AC
-----------------	---------

OUTPUT DATA

Number of contacts	3
Contact material	AgNi
Breaking Voltage	250 V
Breaking capacity current	10 A
Recommended max load	10 A/250 V AC-1; 0,5 A/110 V DC-1
Recommended min load	10 mA/10 V
Resistive load 110 V dc max	55 W
Resistive load 24 V dc max	72 W
Surge current (20 ms)	30 A
Release time	50 ms
Release time + contact debounce	50 ms

GENERAL DATA

IP class	IP40
Isolation contact/contact	2500 V

Isolation contact/coil	2500 V
Insulation class EN60947	250 V Pollution 3, Group C
Temperature operational min	-40 °C
Storage temperature min	-40 °C
Storage temperature max	80 °C
Temperature operational max	60 °C
Frequency	50 Hz
Optional coil	Bistable
Weight	95 g

