OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

RELAY AND PUSH-IN SOCKET SETS

C10A10X230A+S10-PI



- Includes the slimmest sockets on the market
- One part number including the relay and socket
- Saves time during assembly and wiring
- The most common relays available as a set

PRODUCT DESCRIPTION

The most common relays bought by the majority of customers are now available as a relay and socket set, simplifying procurement with only 1 part number for the set. Relays available in 24V DC and 230V AC. The sets save time during assembly and wiring and use the latest push-in sockets from ComatReleco saving 25% more space in your panel.

TECHNICAL DATA

Approvals	CCC, CE, CSA, Gost R, RoHS, UL
Breaking capacity current	10 A
Breaking Voltage	250 V
Coil voltage ac	230 V AC
Contact material	AgNi
Frequency	50 Hz
Insulation class EN60947	250 V (pollution 3, Group C)
IP class	IP40
Mechanical life expectancy	AC:10 Mill./DC:20 Mill
Nominal power ac	1.1 VA
Number of contacts	1
Optional coil	X (LED)
Overvoltage UNX max	1.1
Recommended min load	10 mA / 10 V
Release time	5 ms
Release time + contact debounce	8 ms
Storage temperature max	80 °C
Storage temperature min	-40 °C
Surge current (20 ms)	30 A
Temperature operational max	70 °C

Temperature operational min	-40 °C
Tripping voltage max UN	0.1
Type of relay	Industrial relay