

RELAY AND PUSH-IN SOCKET SETS

C12A21X230A+S12-PI

- Includes the slimmest sockets on the market
- One part number including the relay and socket
- Saves time during assembly and wiring
- The most common relays available as a set



PRODUCT DESCRIPTION

The most common relays bought by the majority of customers are now available as a relay and socket set, simplifying procurement with only 1 part number for the set. Relays available in 24V DC and 230V AC. The sets save time during assembly and wiring and use the latest push-in sockets from ComatRelco saving 25% more space in your panel.

TECHNICAL DATA

Bounce time	1
Breaking capacity current	5 A
Breaking Voltage	250 V
Coil voltage ac	230 V AC
Contact material	AgNi + 0,2 µ Au
Frequency	50 Hz
IP class	IP40
Isolation contact/coil	5000 V
Isolation contact/contact	3000 V
Mechanical life expectancy	AC: 10Mill/. DC: 20 Mill
Nominal power ac	1.1 VA
Number of contacts	2
Optional coil	X (LED)
Overvoltage UNX max	1.1
Recommended max load	5 A/250 V AC 1; 0,5A/110 V DC-1
Recommended min load	10 mA/10 V
Release time	5 ms
Release time + contact debounce	8 ms
Response time	10 ms

Surge current (20 ms)	15 A
Weight	21 g
Voltage min	0.6 V
Working Un	0,8-1,10