

C10 INTERFACE RELAY

1-pole 10 A - IRC

C10T13X48D

Relay 5 Pin 1 Pole Twin 5μ Au LED 48V dc

- Robust flat pins, for industrial applications
- Both mechanical and LED indication
- Colour-coded test button
- Twin contact for low loads



PRODUCT DESCRIPTION

TECHNICAL DATA

INPUT DATA

Nominal power dc	0.7 W
Coil voltage dc	48 V DC
Overvoltage UNX max	1.1
Tripping voltage max UN	0.1

OUTPUT DATA

Number of contacts	1
Contact material	AgNi + 3 μ Au
Breaking Voltage	250 V
Breaking capacity current	6 A
Recommended min load	1 mA / 5 V
Mechanical life expectancy	AC:10 Mill./DC:20 Mill
Surge current (20 ms)	15 A
Release time	5 ms
Release time + contact debounce	8 ms

GENERAL DATA

IP class	IP40
----------	------

Insulation class EN60947	250 V (pollution 3, Group C)
Temperature operational min	-40 °C
Storage temperature min	-40 °C
Storage temperature max	80 °C
Temperature operational max	70 °C
Frequency	50 Hz
Optional coil	X (LED)
Approvals	CCC, CE, CSA US, RoHS, UL, Gost R
Type of relay	Industrial relay

