OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

C9 MINIATURE RELAY

4-pole 5 A - QRC

C9A42X115A
Relay 14 Pin 4 Pole 5µ Au LED 115V ac



- Colour-coded test button, both lockable and non-locking
- Marking system
- Mechanical indication

PRODUCT DESCRIPTION

TECHNICAL DATA

INPUT DATA

Working Un	0,8-1,1
Nominal power ac	1.2 VA
Coil voltage ac	115 V AC
Tripping voltage max UN	0.25

OUTPUT DATA

Number of contacts	4
Contact material	AgNi + 10 µ Au
Breaking Voltage	250 V
Breaking capacity current	5 A
Recommended max load	5 A/250V AC-1; 5 A/30 V DC-1
Recommended min load	1 mA/1 V
Resistive load 110 V dc max	50 W
Resistive load 24 V dc max	100 W
Mechanical life expectancy	AC: 10 Mill./DC: 20 Mill
Surge current (20 ms)	15 A
Release time	6 ms
Release time + contact debounce	7 ms

GENERAL DATA

IP class	IP40
Isolation contact/contact	2500 V
Isolation contact/coil	2000 V
Temperature operational min	-40 °C
Storage temperature min	-40 °C
Storage temperature max	80 °C
Temperature operational max	60 °C
Frequency	50 Hz
Optional coil	X (LED)
Weight	43 g
Approvals	CE, Gost R, RoHS, CCC, CSA, Lloyd´s, UL











