

C10 INTERFACE RELAY

1-pole 10 A - IRC

C10G1024D

Relay 4 Pin 1 Pole N/O 24V dc

- Robust flat pins, for industrial applications
- Both mechanical and LED indication
- Colour-coded test button
- Twin contact for low loads



PRODUCT DESCRIPTION

TECHNICAL DATA

INPUT DATA

Nominal power dc	0.7 W
Coil voltage dc	24 V DC
Overvoltage UNX max	1.1
Tripping voltage max UN	0.1


OUTPUT DATA

Number of contacts	1
Contact material	AgNi
Breaking Voltage	250 V
Breaking capacity current	10 A
Recommended min load	10 mA / 10 V
Mechanical life expectancy	AC:10 Mill./DC:20 Mill
Surge current (20 ms)	30 A
Release time	8 ms
Release time + contact debounce	8 ms

GENERAL DATA


IP class	IP40
----------	------

Insulation class EN60947	250 V (pollution 3, Group C)
Temperature operational min	-40 °C
Storage temperature min	-40 °C
Storage temperature max	80 °C
Temperature operational max	70 °C
Frequency	50 Hz
Approvals	CCC, CE, RoHS, UL, Gost R
Type of relay	Industrial relay




C10-G10

10A 250V AC-1
10A 30V DC-1



A2 — A1

03



CE EAC
Made in India

