
OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

INTERFACE MODULE CRINT

CRINT

CRINT-C111/UC12V
Interface Module 1 x C/O Screw 12V ac/dc



- Relay module up to 6A 250 V
- Solid State modules up to 2A
- Screw or cage clamp terminals
- LED status indication

PRODUCT DESCRIPTION

TECHNICAL DATA

INPUT DATA

Coil voltage	12 AC/DC
Working Un	0,8…1,25

OUTPUT DATA

Number of contacts	1
Contact material	AgSnO2
Recommended min load	100 mA / 12 V
Recommended max load	6 A, 250 V AC-1 / 6 A, 30 V DC-1
Breaking capacity current	6 A
Inrush max	15 A
Switching power AC1 / 230 V	1500 VA
Switching power AC15 / 230 V	300 VA
Breaking capacity DC1 / 30 V	180 W

GENERAL DATA

IP class	IP20
Temperature operational min	-40 °C
Temperature operational max	70 °C
Storage temperature min	-40 °C
Storage temperature max	85 °C

DIMENSIONS & MATERIALS

Material	PA6

