
OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

INTERFACE MODULE CRINT

CRINT

CRINT-C115/DC12V
Interface Module SSR DC N/O Screw 12V dc



- Relay module up to 6A 250 V
- Solid State modules up to 2A
- Screw or cage clamp terminals
- LED status indication


PRODUCT DESCRIPTION


TECHNICAL DATA


GENERAL DATA


Temperature operational min	-30 °C
Temperature operational max	70 °C
Storage temperature min	-40 °C
Storage temperature max	85 °C
Material	PA6


Number of contacts	1
Working Un	0,8…1,25
Recommended max load	2 A, 24 V DC-1
Recommended min load	20 mA / 5 V
Breaking capacity current	2 A
Coil voltage	12 AC/DC
Inrush max	48 A
IP class	IP20



Current [A]
Temperature [C]
2.5
2
1.5
1
0.5
0
0
20
40
60
80
100



12
11
14
A1
A2
89
47
42
TS35
6,2
3,4
73


71.1
59.8
40.2
20.6
35.7
92.7
2.1


12
11
14
A1
A2
94
49,5
40,5
TS35
6,2
3,4
73


12
11
14
A1
A2
89
47
42
TS35
6,2
3,4
73


71.1
59.8
40.2
20.6
35.7
92.7
2.1


12
11
14
A1
A2
94
49,5
40,5
TS35
6,2
3,4
73