**OEM Automatic Ltd**
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# IDEM EMERGENCY STOP (E-STOP) SWITCHES ESL-SS

232012
ESL-SS(P) ½NPT '3NC 1NO'




- Robust stainless steel emergency stop
- IP69K
- -25°C - 80°C
- 3 cable connection positions

**PRODUCT DESCRIPTION**

## TECHNICAL DATA

| | |
|---|---|
| **Annual usage** | 8 cycles per hour/24 hours per day/365 day |
| **Approvals** | EN60947-5-1, EN60947-5-5, EN62061, UL 508, ISO 13850, ISO 13849-1 |
| **ATEX approved** | No |
| **Conduit entry** | 1/2"NPT |
| **Contact type** | EN60947-5-1 double break type Zb Snap Action up to 4NC (positive break) 2NO (Auxiliary) |
| **Contacts** | 3NC 1NO |
| **Housing material** | Stainless steel 316 |
| **Integrated LED indication** | No |
| **IP class** | IP69K |
| **Material contacts** | Silver |
| **Mechanical reliability B10d** | $2.5x10^6$ operations at 100mA load |
| **Mounting** | 4 x M4 |
| **MTTFd** | 214 years |
| **Number of poles** | 4 |
| **Operating temperature** | -25°C +80°C |
| **Operational rating** | 240v 3A |
| **PFHd** | $<1.0 \times 10^{-7}$ |
| **Rated insulation voltage** | 500V |
| **Short circuit overload protection** | Fuse externally 10A(FF) |

| | |
|---|---|
| **Thermal current (Ith)** | 10 A |
| **Withstand voltage** | 2500V |

