

## CONDUCTIVE LEVEL-PROBE - SLP SERIES

00.0008.0053  
 500mm length, 3xelectrodes, G1

- 1 to 4 St. Steel electrodes
- Electrodes length from 100 mm. to 1500 mm.
- Brass, St. Steel, PPL body materials
- Working pressure up to 6 bar
- Working temperature up to 100°C




### PRODUCT DESCRIPTION


The SL conductive probe series provides a solution for controlling the level of liquid with a minimum value of conductivity of 1µs. The probes are available in a wide variety of materials and process connections and are of construction appropriate to operation in extreme conditions such as those found on industrial plants.

## TECHNICAL DATA

Electrical connection	DIN A 43650
Electrode Length	500mm
IP class	IP65
Manufacturer part no.	SLP.25G.3X500.K.S1
Material of coatings on electrodes	PVDF
Material of connection	Polypropylene
Mounting	Vertical
Number of electrodes	3
Pressure max	6 bar
Process connection	G1
Temperature operational max	100 °C



Electrodes length mm. L	500	1000	1500
<b>SW</b> mm	<b>A</b> mm	<b>B</b> mm	
32	63	20	
32	63	20	
40	68	20	
55	68	20	



Electrodes length mm. L	500	1000	1500
<b>SW</b> mm	<b>A</b> mm	<b>B</b> mm	
32	63	20	
32	63	20	
40	68	20	
55	68	20	