

## VALCO - STAINLESS STEEL SIDE MOUNT LEVEL SWITCH - SML SERIES

00.0002.9101

100mm length, SS, NC/NO, 1.5M cable, Max 30 bar

- Standard item side mounting position
- N.1 reed switch contact NA/NC/SPDT
- Maximum working pressure 30 Bar
- Maximum working temperature 110°C
- IP65 protection



### PRODUCT DESCRIPTION

This level switch, with its reduced overall dimensions and simplicity of installation, offers a reliable solution for the control of liquids in all applications where it is necessary to mount a lateral type. The standard version is for installation from inside the tank, on request, execution with possibility of mounting from outside the tank are available

### TECHNICAL DATA

|                             |                        |
|-----------------------------|------------------------|
| Current                     | 0.5AC/0.7DC            |
| Electrical connection       | Pre-cabled 1.5m        |
| Function                    | N/O & N/C              |
| Hysteresis max              | 8 mm                   |
| IP class                    | IP65                   |
| Manufacturer part no.       | L1.S52.SML.3.16.KS.C1L |
| Material of float           | Stainless steel 316    |
| Material of seals           | FKM                    |
| Material of wetted parts    | Stainless steel 316    |
| Process connection          | M16x1.5                |
| Specific gravity            | 0.67                   |
| Temperature operational max | 110 °C                 |
| Voltage                     | 300AC/350DC            |

