

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

VALCO - STAINLESS STEEL SIDE MOUNT LEVEL SWITCH - SML SERIES

senseca

00.0002.9103 100mm length, SS, CO, 1.5M cable, Max 30 bar

- Standard item side mounting position
- N.1 reed switch contact NA/NC/SPDT
- Maximum working pressure 30 Bar
- Maximum working temperature 110°C
- IP65 protection



PRODUCT DESCRIPTION

This level switch, with its reduced overall dimensions and simplicity of installation, offers a reliable solution for the control of liquids in all applications where it is necessary to mount a lateral type. The standard version is for installation from inside the tank, on request, execution with possibility of mounting from outside the tank are available

TECHNICAL DATA

Current	0.5AC/0.5DC
Electrical connection	Pre-cabled 1.5m
Function	Changeover (SPDT)
Hysteresis max	8 mm
IP class	IP65
Manufacturer part no.	L1.S52.SML.7D.16.KS.C1L
Material of float	Stainless steel 316
Material of seals	FKM
Material of seals Material of wetted parts	FKM Stainless steel 316
Material of wetted parts	Stainless steel 316
Material of wetted parts Pressure max	Stainless steel 316 30 bar
Material of wetted parts Pressure max Process connection	Stainless steel 316 30 bar M16x1.5
Material of wetted parts Pressure max Process connection Specific gravity	Stainless steel 316 30 bar M16x1.5 0.67



