
OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

VALCO - SIDE MOUNT LEVEL SWITCH - S50 SERIES

00.0002.5035
Adj. length, Straight rod, SS, 2xCO, Max 25 bar




- PP housing with PG9 electrical connection
- Micro-switch SPDT
- Max working pressure 40 bar
- Max working temperature 180°C
- Brass or St. Steel materials


PRODUCT DESCRIPTION


These level switches, with their reduced dimensions and simplicity of installation, constitute a reliable solution for the control of liquids in all applications where it is necessary to mount a lateral type. Suitable for use with process temperature up to 180 ° C.


TECHNICAL DATA


Current	3A
Electrical connection	PG9 cable gland
Function	Changeover (SPDT)
Hysteresis max	20 mm
IP class	IP65
Manufacturer part no.	L2.S50.7.D.25.G.S.W.I33
Material of body	Glass fiber reinforced plastic (PBT)
Material of float	Stainless steel 316
Material of seals	PTFE
Material of wetted parts	Stainless steel
Mounting	Horizontal
Number of microswitches	2
Pressure max	25 bar
Process connection	G1
Rod type	Straight
Specific gravity	0.7
Temperature operational max	180 °C
Voltage	250Vac/48Vdc



73
90
25
30
NC
NO
uSW1
uSW2
NO
NC
CABLE GLAND


190
170
150
90
1"-GAS
55
62


220
200
180
1"-GAS
ø30
55
62
50


73
90
25
30
NC
NO
uSW1
uSW2
NO
NC
CABLE GLAND


190
170
150
90
1"-GAS
55
62


220
200
180
1"-GAS
ø30
55
62
50