

**VALCO - ADJUSTABLE LEVEL SWITCH,  
VERTICAL MOUNT - KIT.S1 SERIES**

00.0002.3320

Lvl.sw for KIT B45, 4M cable

- 500 mm. to 1500 mm. tube length
- Brass stem and connection, Spansil float
- Max working pressure up to 20 bar
- Max temperature 105°C
- Reed switch SPST or SPDT

**PRODUCT DESCRIPTION**

Modular level switch with 1 electrical contact. The user is able to obtain a level switch of the desired length interposing an extension pipe between the control unit and the process fitting. The electrical contact inside the control unit is sealed and immersion proof. The assembly kit can be selected from a wide series of options that allows the user to adapt it to the most common types of installation.

**TECHNICAL DATA**

|                                    |                              |
|------------------------------------|------------------------------|
| <b>Current</b>                     | 1.3A                         |
| <b>Function</b>                    | N/O & N/C                    |
| <b>IP class</b>                    | IP65                         |
| <b>Manufacturer part no.</b>       | KIT.S1.B45.4.B.25GO.S1.L1.I2 |
| <b>Material of connection</b>      | Brass                        |
| <b>Material of float</b>           | SPANSIL                      |
| <b>Material of seals</b>           | NBR                          |
| <b>Pressure max</b>                | 20 bar                       |
| <b>Process connection</b>          | G1                           |
| <b>Specific gravity</b>            | 0.35                         |
| <b>Temperature operational max</b> | 105 °C                       |
| <b>Voltage</b>                     | 250V                         |

