OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

VISUAL LEVEL INDICATOR - ILV SERIES

00.0016.0033
300mm length, 2xM12 conn.



- 127 mm. to 1000 mm. length
- Aluminium anodized body, other on request
- Working pressure up to 2 bar
- Working temperature up to 80°C
- Acrylic sight and protection tube


PRODUCT DESCRIPTION

The visual level indicators ILC series are used to visually monitor the status of the level of liquids in tanks. The indicators are mounted outside the tank by means of threaded connections. The system thus designed (double vision pipe) allows the vision of the level inside the tank at 360°

TECHNICAL DATA


Length	300 mm
Manufacturer part no.	ILV.0300.D.PX.B
Material of connection	Anodised aluminum
Material of glass tube	PMMA
Material of seals	NBR
Pressure max	2 bar
Process connection	M12
Temperature operational max	80 °C





Connections Ø	Type	Length H mm
2 x M12	ILV – 0120	127
	ILV – 0250	254
	ILV – 0300	300
	ILV – 0350	350
	ILV – 0400	400
	ILV – 0450	450
	ILV – 0500	500
	ILV – 0600	600
	ILV – 0700	700
	ILV – 0800	800
	ILV – 0900	900
	ILV – 1000	1000





Connections Ø	Type	Length H mm
2 x M12	ILV – 0120	127
	ILV – 0250	254
	ILV – 0300	300
	ILV – 0350	350
	ILV – 0400	400
	ILV – 0450	450
	ILV – 0500	500
	ILV – 0600	600
	ILV – 0700	700
	ILV – 0800	800
	ILV – 0900	900
	ILV – 1000	1000