**OEM Automatic Ltd**
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# VISUAL LEVEL INDICATOR - ILV SERIES

00.0016.0061
800mm length, 2xM12 conn.



- 127 mm. to 1000 mm. length
- Aluminium anodized body, other on request
- Working pressure up to 2 bar
- Working temperature up to 80°C
- Acrylic sight and protection tube


### PRODUCT DESCRIPTION

The visual level indicators ILC series are used to visually monitor the status of the level of liquids in tanks. The indicators are mounted outside the tank by means of threaded connections. The system thus designed (double vision pipe) allows the vision of the level inside the tank at 360°

## TECHNICAL DATA


| | |
|---|---|
| **Length** | 800 mm |
| **Manufacturer part no.** | ILV.0800.D.PX.B |
| **Material of connection** | Anodised aluminum |
| **Material of glass tube** | PMMA |
| **Material of seals** | NBR |
| **Pressure max** | 2 bar |
| **Process connection** | M12 |
| **Temperature operational max** | 80 °C |




| Connections Ø | Type | Length H mm |
|---|---|---|
| 2 x M12 | ILV – 0120 | 127 |
| | ILV – 0250 | 254 |
| | ILV – 0300 | 300 |
| | ILV – 0350 | 350 |
| | ILV – 0400 | 400 |
| | ILV – 0450 | 450 |
| | ILV – 0500 | 500 |
| | ILV – 0600 | 600 |
| | ILV – 0700 | 700 |
| | ILV – 0800 | 800 |
| | ILV – 0900 | 900 |
| | ILV – 1000 | 1000 |




| Connections Ø | Type | Length H mm |
|---|---|---|
| 2 x M12 | ILV – 0120 | 127 |
| | ILV – 0250 | 254 |
| | ILV – 0300 | 300 |
| | ILV – 0350 | 350 |
| | ILV – 0400 | 400 |
| | ILV – 0450 | 450 |
| | ILV – 0500 | 500 |
| | ILV – 0600 | 600 |
| | ILV – 0700 | 700 |
| | ILV – 0800 | 800 |
| | ILV – 0900 | 900 |
| | ILV – 1000 | 1000 |