

VISUAL LEVEL INDICATOR - ILV SERIES

00.0016.0041

1000mm length, 2xM12 conn.

- 127 mm. to 1000 mm. length
- Aluminium anodized body, other on request
- Working pressure up to 2 bar
- Working temperature up to 80°C
- Acrylic sight and protection tube





PRODUCT DESCRIPTION

The visual level indicators ILC series are used to visually monitor the status of the level of liquids in tanks. The indicators are mounted outside the tank by means of threaded connections. The system thus designed (double vision pipe) allows the vision of the level inside the tank at 360°

TECHNICAL DATA

Length	1000 mm
Manufacturer part no.	ILV.1000.D.PX.B
Material of connection	Anodised aluminum
Material of glass tube	PMMA
Material of seals	NBR
Pressure max	2 bar
Process connection	M12
Temperature operational max	80 °C

	Connections Ø	Type	Length H mm
		ILV - 0120	127
		ILV - 0250	254
		ILV - 0300	300
		ILV - 0350	350
		ILV - 0400	400
		ILV - 0450	450
		ILV - 0500	500
		ILV - 0600	600
		ILV - 0700	700
		ILV - 0800	800
		ILV - 0900	900
		ILV - 1000	1000
	Connections Ø	Type	Length H mm
		ILV - 0120	127
		ILV - 0250	254
		ILV - 0300	300
		ILV - 0350	350
		ILV - 0400	400
		ILV - 0450	450
		ILV - 0500	500
		ILV - 0600	600
		ILV - 0700	700
		ILV - 0800	800
		ILV - 0900	900
		ILV - 1000	1000

