OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

VISUAL LEVEL INDICATOR - ILC SERIES

00.0016.0065
127mm length, 2xM12 conn., 2xSPST



- Version with switch MIN/MAX
- 127 mm. to 1000 mm. length
- Working pressure up to 2 bar
- Working temperature up to 80°C


PRODUCT DESCRIPTION

The visual level indicators ILC series are used to visually monitor the status of the level of liquids in tanks, and are equipped with a minimum or maximum level switch. The indicators are mounted outside the tank by means of threaded connections. The system thus designed allows the vision of the level inside the tank at 360°.

TECHNICAL DATA

Electrical connection	DIN C 43650 Micro
Length	127 mm
Manufacturer part no.	ILC.0127.L1.48.L2.48.D.PX.B
Material of connection	Anodised aluminum
Material of glass tube	PMMA
Material of seals	NBR
Pressure max	2 bar
Process connection	M12
Temperature operational max	80 °C

Type	H mm	L1 mm	L2 mm
ILC – **0127**	127	48	48
ILC – **0254**	254	48	48
ILC – **0300**	300	48	48
ILC – **0350**	350	48	48
ILC – **0400**	400	48	48
ILC – **0450**	450	48	48
ILC – **0500**	500	48	48
ILC – **0600**	600	48	48
ILC – **0700**	700	48	48
ILC – **0800**	800	48	48
ILC – **0900**	900	48	48
ILC – **1000**	1000	48	48



Type	H mm	L1 mm	L2 mm
ILC – **0127**	127	48	48
ILC – **0254**	254	48	48
ILC – **0300**	300	48	48
ILC – **0350**	350	48	48
ILC – **0400**	400	48	48
ILC – **0450**	450	48	48
ILC – **0500**	500	48	48
ILC – **0600**	600	48	48
ILC – **0700**	700	48	48
ILC – **0800**	800	48	48
ILC – **0900**	900	48	48
ILC – **1000**	1000	48	48

