

## CONDUCTIVE LEVEL-PROBE - SLP SERIES

00.0008.0098

500mm length, 1xelectrode, G3/8

- 1 to 4 St. Steel electrodes
- Electrodes length from 100 mm. to 1500 mm.
- Brass, St. Steel, PPL body materials
- Working pressure up to 6 bar
- Working temperature up to 100°C




### PRODUCT DESCRIPTION

The SL conductive probe series provides a solution for controlling the level of liquid with a minimum value of conductivity of 1µs.


The probes are available in a wide variety of materials and process connections and are of construction appropriate to operation in extreme conditions such as those found on industrial plants.

### TECHNICAL DATA

Electrical connection	DIN A 43650
Electrode Length	500mm
IP class	IP65
Manufacturer part no.	SLP.10G.1X500.K.S1
Material of coatings on electrodes	PVDF
Material of connection	Polypropylene
Mounting	Vertical
Number of electrodes	1
Pressure max	6 bar
Process connection	G3/8
Temperature operational max	100 °C



Electrodes length mm. L	500	1000	1500
SW mm	A mm	B mm	
32	63	20	
32	63	20	
40	68	20	
55	68	20	



Electrodes length mm. L	500	1000	1500
SW mm	A mm	B mm	
32	63	20	
32	63	20	
40	68	20	
55	68	20	