OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

TECNOPLASTIC - FLOAT SWITCH - TAURUS

GTAH3X106GG01
Double function, H07 RNF, 6M cable



- Internal counterweight
- 20 metres maximum depth
- Up to 60°C
- Three chamber design

PRODUCT DESCRIPTION

Unlike traditional floats that float on the water's surface, the Taurus level switch, thanks to its special construction of an integrated counterweight, remains under water.

The Taurus has three watertight chambers meaning it is very robust and reliable in critical applications.
Used alone or in multiples, minimum and maximum levels/high and low alarm outputs can be maintained and adjusted easily.

- Drainage plants
- Pumping stations
- Dirty water systems.

TECHNICAL DATA

Activation angle	20 °
Approvals	CE, EAC, TÜV

Cable length	6 m
Cable type	H07RN-F
Depth max	20 m
Fixing kit included	No
Function	Changeover (SPDT)
Insulation class	I
IP class	IP68
Material of float	Polypropylene
Operating temperature to	50 °C
Rated current	8 A
Specific gravity	0.95 - 1.05 kg/dm³
Supply voltage	250 V











