

## TECNOPLASTIC FLOAT SWITCH TAURUS-FEP

GTAF4G010AA01

Taurus-Chem, FEP 4G0,75, 10M, 2 func

- Internal counterweight
- 20 metres maximum depth
- Up to 80°C
- Three chamber design
- Suitable for use in chemical environments



### PRODUCT DESCRIPTION

Unlike traditional floats that float on the water's surface, the Taurus level switch, thanks to its special construction of an integrated counterweight, remains under water.

The Taurus has three watertight chambers meaning it is very robust and reliable in critical applications.

Used alone or in multiples, minimum and maximum levels/high and low alarm outputs can be maintained and adjusted easily.

Suitable for:

- Immersion in hydrocarbons
- Medical and scientific facilities
- Water purification plants
- Air conditioning plants

### TECHNICAL DATA

|                          |                                |
|--------------------------|--------------------------------|
| Activation angle         | 20 °                           |
| Approvals                | CE                             |
| Cable length             | 10 m                           |
| Cable type               | FEP - FFR105OPR5F 4G0,75       |
| Depth max                | 20 m                           |
| Fixing kit included      | Yes                            |
| Insulation class         | I                              |
| IP class                 | IP68                           |
| Material of float        | Polypropylene                  |
| Operating temperature to | 80 °C                          |
| Rated current            | 8 A                            |
| Specific gravity         | 0.95 - 1.05 kg/dm <sup>3</sup> |

**Supply voltage**

250 V