OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

TECNOPLASTIC FLOAT SWITCH TAURUS-FEP

GTAF4G020AA01
Taurus-Chem, FEP 4G0,75, 20M, 2 func



- Internal counterweight
- 20 metres maximum depth
- Up to 80°C
- Three chamber design
- Suitable for use in chemical environments

PRODUCT DESCRIPTION

Unlike traditional floats that float on the water's surface, the Taurus level switch, thanks to its special construction of an integrated counterweight, remains under water.

The Taurus has three watertight chambers meaning it is very robust and reliable in critical applications.
Used alone or in multiples, minimum and maximum levels/high and low alarm outputs can be maintained and adjusted easily.

Suitable for:

- Immersion in hydrocarbons
- Medical and scientific facilities
- Water purification plants
- Air conditioning plants

TECHNICAL DATA

Activation angle	20 °
Approvals	CE
Cable length	20 m
Cable type	FEP - FFR105OPR5F 4G0,75
Depth max	20 m
Fixing kit included	Yes
Insulation class	I
IP class	IP68
Material of float	Polypropylene
Operating temperature to	80 °C
Rated current	8 A
Specific gravity	0.95 - 1.05 kg/dm³
Supply voltage	250 V