OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

TECNOPLASTIC - FLOAT SWITCH - OLYMPIC 03

GOAH3G105GNB1
Olympic 03,H07 RNF 3G1,5m,1 func,Bambo




- Maximum depth of 20 metres
- 20° Activation Angle
- Bamboo Arm Included
- Up to 50°C


PRODUCT DESCRIPTION


This float switch has an activation angle of 20° for overflow alarm. Constructed with materials very resistant to mechanical stress, it's ideal for applications in turbulent waters as it can help prevent the cable from tangling up so the float can work properly. This can be fitted to wells and tanks with screws (not supplied) or to pipping on pumps of any diameter using the cable ties which are supplied. Assembled with right (recommended) or left orientation, the float switch can be installed in 3 different positions horizontal, vertical, and vertical 180° to allow the regulation of small changes in minimum and maximum level.
This can be used in narrow spaces, sewage, and industrial waters.


TECHNICAL DATA


Activation angle	20 °
Approvals	CE, EAC, TÜV
Cable type	H07RN-F
Depth max	5 m
Insulation class	I
IP class	IP68
Material of float	Polypropylene
Operating temperature to	50 °C
Rated current	10 A
Supply voltage	250 V







ON
OFF


20°


ALARM
ON
OFF


ON
OFF