

## VALCO LCD LEVEL SENSOR

LCD.S40.20.450/500.S.50GS.M12

- Local indicator 4 digit (9999)
- Integrated data logger + export file data .csv
- Up to 6m length
- Analogue output switchable mA or V
- Configured via NFC communication system through "MYVALCO" APP



### PRODUCT DESCRIPTION

The principle operation of the LCD-S level switch is based on the moderate shutdown of a series of resistors and reed contacts. These are placed inside the guiding rod by a magnetic float. The only moving parts will be the float which moves along the measuring rod. You can program the sensor manually or via the "MYVALCO" app using NFC technology, available on Android® app store.

General specifications for continuous level sensor with display. Other specifications are selectable in the part number builder form below.

General specifications for LCD level sensor:

- Local indicator 4 digit (9999)
- Display and electrical connection are independently rotatable 335°/343°
- Analogue output switchable mA or V
- Configured via NFC communication system through the APP
- Integrated data logger + export file data .csv
- Up to 6m length
- Maximum working pressure 50 bar
- Operating ambient temperature -30°C ... +55°C
- Standard working temperature up to 105°C
- Minimum degree of protection IP65

When requesting a quote or speaking to a member of our team please specify the measuring length and total length you would like as this is customisable, the data below is based on a total length of 500mm and measuring length of 450mm.

Need Help? [Email our Pressure & Flow team](#) or call us for more information 0116 284 9900.

### TECHNICAL DATA

IP class	IP65
Length overall	500 mm
Material of connection	AISI 316
Material of float	Stainless steel 316
Measuring length	450 mm

Measuring resolution	20
Pressure max	15 bar
Process connection	2" UNI 228/1
Specific gravity	0.78
Temperature operational max	105 °C