

**KUEBLER - ABSOLUTE-CODED  
 ANGULAR TRANSMITTER SENDIX  
 5858/5878, OPTICAL, PROFINET, Ø58 MM  
 SERIE 5858 PROFINET**



- Housing diameter Ø58 mm
- ProfiNet
- Safety-Lock™
- High enclosure class

**PRODUCT DESCRIPTION**

Sendix 5858/5878 is a one-way fieldbus sensor with ProfiNet in robust design. Thanks to the design of Safety-Lock™ and the fully cast housing, the sensor is able to handle even the more demanding applications where there are high demands on the sensor. The wide temperature range combined with the high enclosure class allows the sensor to be used outdoors as well as applications where large temperature changes occur. Sendix 5858/5878 is available with LED indication, which facilitates diagnosis of the sensor and a set button that facilitates calibration.

Please refer to the images below for ordering information.





<b>Order code</b>	<b>8.5858</b>	<b>.XXC2</b>	<b>.C2 12</b>
<b>Shaft version</b>	Type	a b c d	e
<b>a Flange</b>	<b>b Shaft (ø x L), with flat</b>	<b>c Interface / power supply</b>	<b>e Field bus profile</b>
1 = clamping flange, IP65 ø 58 mm [2.28"]	1 = 6 x 10 mm [0.24 x 0.39"] <sup>1)</sup>	<b>C = PROFINET IO / 10 ... 30 V DC</b>	<b>C2 = PROFINET IO</b>
3 = clamping flange, IP67 ø 58 mm [2.28"]	2 = 10 x 20 mm [0.39 x 0.79"] <sup>2)</sup>		
2 = synchro flange, IP65 ø 58 mm [2.28"]	3 = 1/4" x 7/8"	<b>d Type of connection</b>	<i>Optional on request</i>
4 = synchro flange, IP67 ø 58 mm [2.28"]	4 = 3/8" x 7/8"	removable bus terminal cover	- Ex 2/22
5 = square flange, IP65 □ 63.5 mm [2.5"]		<b>2 = 3 x M12 connector, 4-pin</b>	- surface protection salt spray tested
7 = square flange, IP67 □ 63.5 mm [2.5"]			

<b>Order code</b>	<b>8.5878</b>	<b>.XXC2</b>	<b>.C2 12</b>
<b>Hollow shaft</b>	Type	a b c d	e
<b>a Flange</b>	<b>b Blind hollow shaft</b>	<b>c Interface / power supply</b>	<b>e Field bus profile</b>
1 = with spring element, long, IP65	(insertion depth max. 30 mm [1.18"])	<b>C = PROFINET IO / 10 ... 30 V DC</b>	<b>C2 = PROFINET IO</b>
2 = with spring element, long, IP67	3 = ø 10 mm [0.39"]		
3 = with stator coupling, IP65 ø 65 mm [2.56"]	4 = ø 12 mm [0.47"]	<b>d Type of connection</b>	<i>Optional on request</i>
4 = with stator coupling, IP67 ø 65 mm [2.56"]	5 = ø 14 mm [0.55"]	removable bus terminal cover	- Ex 2/22
5 = with stator coupling, IP65 ø 63 mm [2.48"]	6 = ø 15 mm [0.59"]	<b>2 = 3 x M12 connector, 4-pin</b>	- surface protection salt spray tested
6 = with stator coupling, IP67 ø 63 mm [2.48"]	8 = ø 3/8"		
	9 = ø 1/2"		

**TECHNICAL DATA**

<b>Connection</b>	M12
<b>Housing diameter</b>	58 mm
<b>IP class</b>	IP65, IP67
<b>Mounting</b>	Shoulder

<b>Output</b>	ProfiNet
<b>Sensor type</b>	Absolute
<b>Shaft diameter max</b>	10 mm
<b>Shaft diameter min</b>	6 mm
<b>Supply voltage dc max</b>	30 V DC
<b>Supply voltage dc min</b>	10 V DC
<b>Temperature operational max</b>	80 °C
<b>Temperature operational min</b>	-40 °C
<b>Version</b>	Singleturn



Type of connection: 2-D coded


Direction	A1/Port				Port 2			
	Transmit data	Receive data	Transmit data	Receive data	Transmit data	Receive data	Transmit data	Receive data
Signal	TxD+	RxD+	TxD-	RxD-	TxD+	RxD+	TxD-	RxD-
MI2/PIB assignment	1	2	3	4	1	2	3	4

Port A and B



Terminal assignment power supply

Signal	+Vs	n.c.	0V	n.c.
	power supply	-	-	-
Abbreviation	+Vs	-	0V	-
MI2/PIB assignment	1	2	3	4



Type of connection: 2-D coded

Direction	A1/Port				Port 2			
	Transmit data	Receive data	Transmit data	Receive data	Transmit data	Receive data	Transmit data	Receive data
Signal	TxD+	RxD+	TxD-	RxD-	TxD+	RxD+	TxD-	RxD-
MI2/PIB assignment	1	2	3	4	1	2	3	4

Port A and B



Terminal assignment power supply

Signal	+Vs	n.c.	0V	n.c.
	power supply	-	-	-
Abbreviation	+Vs	-	0V	-
MI2/PIB assignment	1	2	3	4

