

## KUEBLER - ABSOLUTE-CODED ANGULAR TRANSMITTER SENDIX 5868/5888, OPTICAL, ETHERCAT, Ø58 MM

SERIE 5888 ETHERCAT

- Housing diameter Ø58 mm
- EtherCAT
- Safety-Lock™
- High enclosure class



### PRODUCT DESCRIPTION

Sendix 5868/5888 is a multifarious sensor with EtherCAT in robust design. Thanks to the construction of Safety-Lock™ as well as the fully cast housing, the sensor is able to handle even the more demanding applications where there are high demands on the sensor. The wide temperature range combined with the high enclosure class allows the sensor to be used both outdoors and in applications where large temperature changes occur

Please refer to the image below for ordering information.

Order code	8.5868	. XXB2 . B2 12
Shaft version	Type	a b c d e
<b>a Flange</b>		
1 = clamping flange, IP65 ø 58 mm [2.28"]		
3 = clamping flange, IP67 ø 58 mm [2.28"]		
2 = synchro flange, IP65 ø 58 mm [2.28"]		
4 = synchro flange, IP67 ø 58 mm [2.28"]		
5 = square flange, IP65 □ 63.5 mm [2.5"]		
7 = square flange, IP67 □ 63.5 mm [2.5"]		
<b>b Shaft (ø x L), with flat</b>		
1 = 6 x 10 mm [0.24 x 0.39"] <sup>1)</sup>		
2 = 10 x 20 mm [0.39 x 0.79"] <sup>2)</sup>		
3 = 1/4" x 7/8"		
4 = 3/8" x 7/8"		
<b>c Interface / power supply</b>		
B = EtherCAT / 10 ... 30 V DC		
<b>d Type of connection</b>		
removable bus terminal cover		
2 = 3 x M12 connector, 4-pin		
<b>e Fieldbus profile</b>		
B2= EtherCAT with CoE (CAN over EtherNet)		
		Optional on request
		- Ex 2/22
		- surface protection
		salt spray tested

Order code	8.5888	. XXB2 . B2 12
Hollow shaft	Type	a b c d e
<b>a Flange</b>		
1 = with spring element, long, IP65		
2 = with spring element, long, IP67		
3 = with stator coupling, IP65 ø 65 mm [2.56"]		
4 = with stator coupling, IP67 ø 65 mm [2.56"]		
5 = with stator coupling, IP65 ø 63 mm [2.48"]		
6 = with stator coupling, IP67 ø 63 mm [2.48"]		
<b>b Blind hollow shaft (insertion depth max. 30 mm [1.18"])</b>		
3 = ø 10 mm [0.39"]		
4 = ø 12 mm [0.47"]		
5 = ø 14 mm [0.55"]		
6 = ø 15 mm [0.59"]		
8 = ø 3/8"		
9 = ø 1/2"		
<b>c Interface / power supply</b>		
B = EtherCAT / 10 ... 30 V DC		
<b>d Type of connection</b>		
removable bus terminal cover		
2 = 3 x M12 connector, 4-pin		
<b>e Fieldbus profile</b>		
B2= EtherCAT with CoE (CAN over EtherNet)		
		Optional on request
		- Ex 2/22
		- surface protection
		salt spray tested

### TECHNICAL DATA

Connection	M12
Housing diameter	58 mm
IP class	IP65, IP67

