

KUEBLER - ABSOLUTE-CODED ANGULAR TRANSMITTER SENDIX M3663 / M3683, MAGNETIC, SSI, Ø36 MM

SERIE M3663

- Housing diameter Ø36 mm
- SSI - interface
- New multicolor technology
- IP67



PRODUCT DESCRIPTION

Sendix M3663 / M3683 is a magnetically encoded absolute encoder with the latest in multicolor technology with "Energy Harvesting". Energy Harvesting technology is based on magnetic recharging, eliminating both battery and gear.

With its magnetic coding, the pulse sensor becomes more shockproof and insensitive. The high IP rating allows the Sendix M3663 / M3683 for outdoor environments and mobile applications.

Please refer to the images below for ordering information.

Order code	8.M3663	.XX2X	.XXXX2
Shaft version	Type	a b c d	e f g

<p>a Flange</p> <p>1 = clamping flange, IP67, ø 36 mm [1.42"]</p> <p>3 = clamping flange, IP65, ø 36 mm [1.42"]</p> <p>2 = synchro flange, IP67, ø 36 mm [1.42"]</p> <p>4 = synchro flange, IP65, ø 36 mm [1.42"]</p> <p>b Shaft (ø x L), with flat</p> <p>1 = ø 6 x 12.5 mm [0.24 x 0.49"]</p> <p>3 = ø 8 x 15 mm [0.32 x 0.59"]</p> <p>5 = ø 10 x 20 mm [0.39 x 0.79"]</p> <p>2 = ø 1/4" x 12.5 mm [0.49"]</p> <p>c Interface / power supply</p> <p>2 = SSI / 10 ... 30 V DC</p>	<p>d Type of connection</p> <p>1 = axial cable, 1 m [3.28'] PUR</p> <p>A = axial cable, special length PUR *)</p> <p>2 = radial cable, 1 m [3.28'] PUR</p> <p>B = radial cable, special length PUR *)</p> <p>3 = axial M12 connector, 8-pin</p> <p>4 = radial M12 connector, 8-pin</p> <p>*) Available special lengths (connection types A, B): 2, 3, 5, 8, 10, 15 m [5.56, 9.84, 16.40, 26.25, 32.80, 49.21'] order code expansion .XXXX = length in dm ex.: 8.M3663.432A.G322.0030 (for cable length 3 m)</p> <p>e Code</p> <p>B = SSI, binary</p> <p>G = SSI, gray</p>	<p>f Resolution (singleturn)</p> <p>A = 10 bit ST</p> <p>2 = 12 bit ST</p> <p>3 = 13 bit ST</p> <p>4 = 14 bit ST</p> <p>g Resolution (multiturn)</p> <p>2 = 12 bit MT</p> <p>6 = 16 bit MT</p> <p>A = 20 bit MT</p> <p>4 = 24 bit MT</p> <p><i>Optional on request</i></p> <ul style="list-style-type: none"> - Ex 2/22 (only for connection types 3 and 4) - surface protection salt spray tested
---	--	--

Order code	8.M3683	.XX2X	.XXXX2
Hollow shaft	Type	a b c d	e f g

<p>a Flange</p> <p>2 = with stator coupling, IP65, ø 46 mm [1.81"]</p> <p>3 = with spring element, long, IP65</p> <p>5 = with stator coupling, IP67, ø 46 mm [1.81"]</p> <p>6 = with spring element, long, IP67</p> <p>b Blind hollow shaft (insertion depth max. 18.5 mm [0.73"])</p> <p>1 = ø 6 mm [0.24"]</p> <p>3 = ø 8 mm [0.32"]</p> <p>4 = ø 10 mm [0.39"]</p> <p>2 = ø 1/4"</p> <p>c Interface / power supply</p> <p>2 = SSI / 10 ... 30 V DC</p>	<p>d Type of connection</p> <p>1 = axial cable, 1 m [3.28'] PUR</p> <p>A = axial cable, special length PUR *)</p> <p>2 = radial cable, 1 m [3.28'] PUR</p> <p>B = radial cable, special length PUR *)</p> <p>3 = axial M12 connector, 8-pin</p> <p>4 = radial M12 connector, 8-pin</p> <p>*) Available special lengths (connection types A, B): 2, 3, 5, 8, 10, 15 m [5.56, 9.84, 16.40, 26.25, 32.80, 49.21'] order code expansion .XXXX = length in dm ex.: 8.M3683.242A.G322.0030 (for cable length 3 m)</p> <p>e Code</p> <p>B = SSI, binary</p> <p>G = SSI, gray</p>	<p>f Resolution (singleturn)</p> <p>A = 10 bit ST</p> <p>2 = 12 bit ST</p> <p>3 = 13 bit ST</p> <p>4 = 14 bit ST</p> <p>g Resolution (multiturn)</p> <p>2 = 12 bit MT</p> <p>6 = 16 bit MT</p> <p>A = 20 bit MT</p> <p>4 = 24 bit MT</p> <p><i>Optional on request</i></p> <ul style="list-style-type: none"> - Ex 2/22 (only for connection types 3 and 4) - surface protection salt spray tested
--	--	--

