

KUEBLER - ABSOLUTE-CODED ANGULAR TRANSMITTER SENDIX M3668R, MAGNETIC, CANOPEN, Ø36 MM

SERIE M3668R SS

- Housing diameter Ø36 mm
- CANopen
- Up to IP69K
- Stainless steel



PRODUCT DESCRIPTION

Sendix M3668R is a magnetically encoded absolute encoder with the latest in multi-field technology with "Energy Harvesting". Energy Harvesting technology is based on magnetic recharging, eliminating both battery and gear.

In addition to multi-color technology, the M3668R has been equipped with extra strong ball bearings and secure attachments, also known as "Safety-Lockplus™".

A unique multifarve pulse sensor with high IP classifications: IP66, IP67 and IP69K, available in stainless steel (V4A).



Please refer to the image below for ordering information.

Order code		8.M3668R.XX2X.2122									
Shaft version		Type	a	b	c	d	e				
a	Version	1 = standard ¹⁾									
		clamping flange ø 42 mm [1.65"]									
	7 = stainless steel V4A ²⁾										
	clamping flange ø 42 mm [1.65"]										
	all metal parts accessible from outside										
	are out of stainless steel V4A										
b	Shaft (ø x L), with flat										
	1 = ø 6 x 12.5 mm [0.24 x 0.49"]										
	3 = ø 8 x 15 mm [0.32 x 0.59"]										
	5 = ø 10 x 20 mm [0.39 x 0.79"]										
	2 = ø 1/4" x 12.5 mm [0.49"]										
	E = ø 10 x 20 mm [0.39 x 0.79"],										
	stainless steel V4A										
c	Interface / power supply	2 = CANopen DS301 V4.2 / 10 ... 30 V DC									
d	Type of connection										
	2 = radial cable, 1 m [3.28'] PVC										
	B = radial cable, special length PVC *)										
	4 = radial M12 connector, 5-pin										
*) Available special lengths (connection type B):											
	2, 3, 5, 8, 10, 15 m [5.56, 9.84, 16.40, 26.25, 32.80, 49.21']										
	order code expansion .XXXX = length in dm										
	ex.: 8.M3668.132B.2122.0030 (for cable length 3 m)										
e	Fieldbus profile	21 = CANopen									
	Optional on request										
	- Ex 2/22 (only for connection type 4)										
	- other shaft diameters out of V4A										
	stainless steel										

TECHNICAL DATA

Connection	M12
Housing diameter	36 mm
IP class	IP66, IP67, IP69K
Mounting	Shoulder
Output	CANopen
Resolution MT	Max. 24 bit

Sensor type	Absolute
Shaft diameter max	10 mm
Shaft diameter min	10 mm
Supply voltage dc max	30 V DC
Supply voltage dc min	10 V DC
Temperature operational max	85 °C
Temperature operational min	-40 °C
Version	Multiturn



Interface	Type of connection	Cable (isolate unused wires individually before initial start-up)					
2	2-B	Signal	-V	0 V	CAN_GND	CAN_H	CAN_L
		Cable colour	BN	WH	GY	GN	YE

Interface	Type of connection	M12 connector, 5-pin					
2	4	Signal	-V	0 V	CAN_GND	CAN_H	CAN_L
		Pin	2	3	1	4	5



Interface	Type of connection	Cable (isolate unused wires individually before initial start-up)					
2	2-B	Signal	-V	0 V	CAN_GND	CAN_H	CAN_L
		Cable colour	BN	WH	GY	GN	YE

Interface	Type of connection	M12 connector, 5-pin					
2	4	Signal	-V	0 V	CAN_GND	CAN_H	CAN_L
		Pin	2	3	1	4	5

