OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

KUEBLER - ABSOLUTE-CODED ANGULAR TRANSMITTER SENDIX F5868 / F5888, OPTICAL, ETHERNET/IP, Ø58 MM

SERIE F5868 ETHERNET/IP



- Housing diameter Ø58 mm
- EtherNet/IP
- Safety-Lock™
- Quick startup

PRODUCT DESCRIPTION

Sendix F5868 / F5888 is a multivalued fieldbus transducer with EtherNet / IP in robust design. Thanks to the construction of Safety-Lock ™ as well as the fully cast housing, the sensor is able to handle even the more demanding applications where there are high demands on the sensor. The wide temperature range combined with the high enclosure class allows the sensor to be used outdoors as well as applications where large temperature changes occur. Sendix F5868 / F5888 comes with LED indication which facilitates diagnosis of the sensor.

Please refer to the images below for ordering information.

Order code Shaft version — 8.F5868 . X X A N . A2 2 2 (Type; a b c d; e)

a *Flange*
1 = clamping flange, IP65 ø 58 mm [2.28"]
2 = synchro flange, IP65 ø 58 mm [2.28"]
5 = square flange, IP65 □63.5 mm [2.5"]

b *Shaft (ø x L), with flat*
1 = 6 x 10 mm [0.24 x 0.39"]
2 = 10 x 20 mm [0.39 x 0.79"]
3 = 1/4" x 7/8"
4 = 3/8" x 7/8"

c *Interface / Power supply*
A = EtherNet IP / 10 ... 30 V DC

d *Type of connection*
N = 3 x axial M12 connector, 4-pin

e *Fieldbus profile*
A2 = EtherNet/IP

Optional on request
- Ex 2/22

Order code Hollow shaft — 8.F5888 . X X A N . A2 2 2 (Type; a b c d; e)

a *Flange*
1 = with spring element long, IP65
3 = with stator coupling, IP65 ø 65 mm [2.56"]
5 = with stator coupling, IP65 ø 63 mm [2.48"]

b *Blind hollow shaft (insertion depth max. 30 mm [1.18"])*
A = ø 10 mm [0.39"]
B = ø 12 mm [0.47"]
C = ø 14 mm [0.55"]
D = ø 15 mm [0.59"]
E = ø 3/8"
F = ø 1/2"

c *Interface / Power supply*
A = EtherNet IP / 10 ... 30 V DC

d *Type of connection*
N = 3 x axial M12 connector, 4-pin

e *Fieldbus profile*
A2 = EtherNet/IP

Optional on request
- Ex 2/22

;

TECHNICAL DATA

Connection	M12
Housing diameter	58 mm

IP class	IP65
Mounting	Shoulder
Output	EtherNet/IP
Resolution MT	Max. 16 bit
Sensor type	Absolute
Shaft diameter max	10 mm
Shaft diameter min	6 mm
Supply voltage dc max	30 V DC
Supply voltage dc min	10 V DC
Temperature operational max	80 °C
Temperature operational min	-40 °C
Version	Multiturn

