

ADVANCED ILLUMINATION AL143 AREA LIGHTING

2x3 spot light

AL143-395C5

Ai General Purpose Spot Light, UV 395, pulsar connector

- Bright area lighting for long distances or large work areas
- Compact design - only 28 mm high
- M6 nut ducts for easy installation



PRODUCT DESCRIPTION

The AL143 spot/bar light is in a 2x3 design, available in a wide range of wavelengths and multiple lens options. It is the ideal illumination for medium working distances, with convenient mounting with an M4 nut channel.

Power options include:

- C1 connector - for use with DCS series controllers
- C5 connector - for use with Pulsar 320 strobe controller
- Continuous in-line controller - powered by 24V power supply
- Combination strobe/continuous in-line controller - powered by 24V power supply
- Default-OFF strobe/continuous in-line controller - powered by 24V power supply
- Flying/tinned leads - powered by 24V power supply

Other Wavelength options:

- UV - 365, 375, 385, 395, 405
- Royal blue - 455
- Blue - 470
- Cyan - 505
- Green - 530
- Amber - 590
- Red orange - 625
- Infrared - 730, 850, 940
- White - WHI

For enquiries or quotes for wavelength and power options not listed here please [contact us](#).

TECHNICAL DATA

TECHNICAL DATA

| | |
|--------------------------------------|-------------------------|
| Wavelength | 395 |
| Colour | Ultraviolet |
| Length | 92.1 mm |
| Connector/controller | C5 connector |
| Standard cable length | Up to 2 meters |
| Photobiological risk factor IEC 6247 | Group 2 (moderate risk) |

| | |
|-----------------------|---------------------|
| Operating temperature | 0 - 60°C |
| Approvals | IEC 62471, CE, RoHS |
| IP class | IP65 |
| Weight | 140.6 g |

