

ADVANCED ILLUMINATION AL4424 BALA BAR LIGHT

Broad Area Linear Array 4"

AL4424-47024

Ai BALA Bar Light, 4", Blue, 24V

- Developed to handle a long, wide field with low angle of view
- Very even lighting throughout the area
- Legacy product see AL150



PRODUCT DESCRIPTION

The AL4424 range of BALA (Broad Area Linear Array) bar lights are legacy part number derived from the AL150 range.

Designed for applications that require broad illumination over a wide area, or for applications requiring an even broader field of illumination, utilise 2 BALA bar lights in parallel.

The AL4424 bar light series is expandable in 1" increments up to 82".

Power options include:

- C1 connector - for use with DCS series controllers
- C5 connector - for use with Pulsar 320 strobe controller
- Continuous in-line controller - powered by 24V power supply
- Combination strobe/continuous in-line controller - powered by 24V power supply
- Default-OFF strobe/continuous in-line controller - powered by 24V power supply
- Flying/tinned leads - powered by 24V power supply

Other Wavelength options:

- UV - 395
- Blue - 470
- Green - 520
- Red - 625, 660
- Infrared - 880
- White - WHI

For enquiries or quotes for sizes and power options not listed here please [contact us](#).

TECHNICAL DATA

TECHNICAL DATA

Wavelength	470
Colour	Blue
Length	117 mm
Width	34 mm

Connector/controller	Flying/tinned leads
Standard cable length	Up to 2 meters
Photobiological risk factor IEC 6247	Group 1 (low risk)
Operating temperature	0 - 60°C
Approvals	IEC 62471, CE, RoHS
IP class	IP50
Weight	157.8 g

