

ADVANCED ILLUMINATION AL46120 - BALA BAR LIGHT

20" Broad Area Linear Array

AL46120-WHI24
Ai BALA Bar Light, 20", White, 24V



- Developed to handle a long, wide field with low angle of view
- Very even lighting throughout the area
- Legacy product see AL150

PRODUCT DESCRIPTION

The AL46120 range of BALA (Broad Area Linear Array) bar lights are legacy part number derived from the AL150 range. Designed for applications that require broad illumination over a wide area, or for applications requiring an even broader field of illumination, utilise 2 BALA bar lights in parallel.
The AL46120 bar light series is expandable in 1" increments up to 82".

Power options include:

- C1 connector - for use with DCS series controllers
- C5 connector - for use with Pulsar 320 strobe controller
- Continuous in-line controller - powered by 24V power supply
- Combination strobe/continuous in-line controller - powered by 24V power supply
- Default-OFF strobe/continuous in-line controller - powered by 24V power supply
- Flying/tinned leads - powered by 24V power supply

Other Wavelength options:

- UV - 395
- Blue - 470
- Green - 520
- Red - 625, 660
- Infrared - 880
- White - WHI

For enquiries or quotes for sizes and power options not listed here please [contact us](#).

TECHNICAL DATA

TECHNICAL DATA

Wavelength	WHI
Colour	White
Length	535 mm
Width	34 mm
Connector/controller	Flying/tinned leads
Operating temperature	0 - 60°C
Approvals	CE, RoHS, IEC
IP class	IP50

Weight

508.9 g

