

## **OEM Automatic Ltd**

Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# ADVANCED ILLUMINATION BL-S050075 BACK LIGHT

EuroBrite Strobe /Continuous Backlight

BL-S050075-850 Ai EuroBrite™ Backlight, Small, infrared 850

- Cost-effective, feature-rich design
- On-board smart driver seamless strobe or continuous
- Robust, sealed IP67 enclosure
- Easy M12X1 connection





### PRODUCT DESCRIPTION

With complete built in control for continuous and strobe modes, the Eurobrite™ range outdoes the comptetition in many ways.

One major feature of the Eurobrite™ is Adaptive Power™ which utilizes an onboard thermistor to maximize light output in continuous mode. As well as Adaptive Power™ to provide maximal output pulse in strobe mode regardless of the exposure period.

#### Additional features:

- IP67 sealed enclosure suitable for washdown environments
- Rugged construction that has been tested to withstand over 1000lb
- Industrial grade LEDs providing high-intensity surface illumination of 38klux

For other wavelength options not listed here please contact us.

## **TECHNICAL DATA**

## **TECHNICAL DATA**

| Wavelength                           | 850   |
|--------------------------------------|---|
| Colour                               | Infrared  |
| Length                               | 75 mm   |
| Width                                | 89 mm   |
| Connector/controller                 | Strobe  |
| Standard cable length                | No cable included, use standard coded 5-pin M12 |
| Photobiological risk factor IEC 6247 | Group 1 (low risk)                              |
| Operating temperature                | 0°C - 60°C                                      |
| Approvals                            | IEC 62471, CE, RoHS                             |
| IP class                             | IP67  |
| Weight                               | 92.53 g   |

