

EFFILUX EFFI-FLEX MODULAR BAR LIGHT

Adjustable beam angle LED bar

FLEX-3-365-SD-P0

Bar light, 3LED, 95mm, UV 365, semi diffuse, no lens



- Intense and uniform illuminated area
- Continuous or strobe mode
- Full range of colors: from UV to IR, white, tricolor
- Adjustable illumination angles (4 angles) & different projection windows

PRODUCT DESCRIPTION

EFFI-Flex is a product that suits your needs with different lens adjustment positions. It 's an adjustable product in terme of wavelength, a compact and easy to install product.

The EFFI-Flex led bars are fitted with high power LED. Through its diffusers (transparent, semi-diffuse and opaline) and polarizers, EFFI-Flex provides a directional, darkfield or diffuse lighting adapted to many machine vision applications.

TECHNICAL DATA

TECHNICAL DATA

Wavelength	365
Colour	Ultraviolet
Length	95 mm
Width	51 mm
Connector/controller	M12 - 4 pins
Supply voltage	24 V DC
Operating temperature	0°C - 50°C
Approvals	CE, RoHS
IP class	IP50
Optional linescan filter	Yes
Optional polarising filter	Yes
Number of LEDs	3
Lens type	Semi-diffusive
Angle of emission	90 °
Housing material	Aluminium

