OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

EFFILUX EFFI-FLEX MODULAR BAR LIGHT

Adjustable beam angle LED bar

FLEX-10-465-TR-P3
Bar light, 10LED, 235mm, Blue 465,transparent, 10°



- Intense and uniform illuminated area
- Continuous or strobe mode
- Full range of colors: from UV to IR, white, tricolor
- Adjustable illumination angles (4 angles) & different projection windows

PRODUCT DESCRIPTION

EFFI-Flex is a product that suits your needs with different lens adjustment positions. It 's an adjustable product in terme of wavelength, a compact and easy to install product.

The EFFI-Flex led bars are fitted with high power LED. Through its diffusers (transparent, semi-diffuse and opaline) and polarizers, EFFI-Flex provides a directional, darkfield or diffuse lighting adapted to many machine vision applications.

TECHNICAL DATA

TECHNICAL DATA

Wavelength	465
Colour	Blue
Length	235 mm
Width	51 mm
Connector/controller	M12 - 4 pins
Supply voltage	24 V DC
Operating temperature	0°C - 50°C
Approvals	CE, RoHS
IP class	IP50

Optional linescan filter	Yes
Optional polarising filter	Yes
Number of LEDs	10
Lens type	Transparent
Angle of emission	10 °
Housing material	Aluminium