

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# **EFFILUX EFFI-SMART LED BAR LIGHT**

Double row LED bar light

SMART-06-525-OP-P2 2 row bar light, 6 LED, Green 525, opaline, 25°

- Chainable: Double I/O connectors
- Auto-strobe
- Built in driver
- Waterproof (IP67)



### PRODUCT DESCRIPTION

The EFFI-SMART is a duel row high power LED bar light, with a choice of 3 diffuser plates (clear, semi-diffuse, diffuse) so the user can create a suitable balence between power and homegeneity.

Integrated controller for dimming or auto-strobe functionality, offering 700% increased intensity in strobe mode as compared to continuous operation. To overcome challenging working environments the EFFI-SMART has a robust design with IP67 rating.

The highly flexible design allows users to easily adjust lens positioning and diffuser plates when necessary.

Other wavelengths and lengths available, contact us for more information.

# **TECHNICAL DATA**

## **TECHNICAL DATA**

Wavelength	525	
Colour	Green	
Length	66 mm	
Width	70 mm	
Connector/controller	2 x M12 5 contacts (1 male & 1 female)	
Supply voltage	24 V DC	
Operating temperature	0°C - 45°C	
Approvals	CE, RoHS	
IP class	IP67	
Optional linescan filter	Yes	
Optional polarising filter	Yes	
Number of LEDs	6	
Lens type	Opaline	
Angle of emission	25 °	
Optional linescan filter Optional polarising filter Number of LEDs Lens type	Yes Yes 6 Opaline	

н	ousing	ı mate	rial

Aluminium