

## ADVANCED ILLUMINATION LL174 LINEAR LIGHT

Expandable High Power Lighting

LL174-505C5  
LL174 bar light, 6", Cyan 505, C5 connector

- Developed for large areas or Line scan applications
- Available in increments of 152 mm (6 inches) up to 1 219 mm (48 inches)



### PRODUCT DESCRIPTION

The LL174 is a high intensity bar light with a large degree of customisation. Available in 16 wavelengths, expandable up to 84" in 6" increments. There is optional heat sink for higher performance and/or high ambient temperature. 3 different lens options are also available, arrow, medium and wide beam spreads.

Power options include:

- C1 connector - for use with DCS series controllers
- C5 connector - for use with Pulsar 320 strobe controller
- Continuous in-line controller - powered by 24V power supply
- Combination strobe/continuous in-line controller - powered by 24V power supply
- Default-OFF strobe/continuous in-line controller - powered by 24V power supply
- Flying/tinned leads - powered by 24V power supply

All Wavelength options:

- UV - 365, 375, 385, 395
- Violet - 405
- Royal blue - 455
- Blue - 470
- Cyan - 505
- Green - 530
- Amber - 590
- Red orange - 625
- Red - 660
- Infrared - 730, 850, 940
- White - WHI

For enquiries or quotes for sizes and power options not listed here please [contact us](#).

## TECHNICAL DATA

### TECHNICAL DATA

Wavelength	505
Colour	Cyan
Length	174 mm

<b>Width</b>	34 mm
<b>Connector/controller</b>	C5 connector
<b>Standard cable length</b>	Up to 2 meters
<b>Photobiological risk factor IEC 6247</b>	Group 1 (low risk)
<b>Operating temperature</b>	0°C - 60°C
<b>Approvals</b>	IEC 62471, CE, RoHS
<b>IP class</b>	IP65
<b>Weight</b>	195.1 g

LL174		
ROD TYPE	NOV-RALED	RALED
LL174	175.0 (6.89)	176.0 (6.93)
LL17412	126.1 (12.84)	129.2 (12.96)
LL17413	478.6 (18.84)	481.7 (18.96)
LL17430	783.4 (30.84)	786.5 (30.96)
LL17436	935.4 (36.84)	938.5 (36.96)
LL17442	1088.2 (42.84)	1091.3 (42.96)
LL17448	1240.8 (48.84)	1243.7 (48.96)
LL17454	1393.0 (54.84)	1396.1 (54.96)
LL17460	1545.4 (60.84)	1548.5 (60.96)
LL17466	1697.8 (66.84)	1700.9 (66.96)
LL17472	1850.2 (72.84)	1853.3 (72.96)
LL17478	2002.6 (78.84)	2005.7 (78.96)
LL17484	2155.0 (84.84)	2158.1 (84.96)
(LENGTH IN MM) (INCHES)		



LL174		
ROD TYPE	NOV-RALED	RALED
LL174	175.0 (6.89)	176.0 (6.93)
LL17412	126.1 (12.84)	129.2 (12.96)
LL17413	478.6 (18.84)	481.7 (18.96)
LL17430	783.4 (30.84)	786.5 (30.96)
LL17436	935.4 (36.84)	938.5 (36.96)
LL17442	1088.2 (42.84)	1091.3 (42.96)
LL17448	1240.8 (48.84)	1243.7 (48.96)
LL17454	1393.0 (54.84)	1396.1 (54.96)
LL17460	1545.4 (60.84)	1548.5 (60.96)
LL17466	1697.8 (66.84)	1700.9 (66.96)
LL17472	1850.2 (72.84)	1853.3 (72.96)
LL17478	2002.6 (78.84)	2005.7 (78.96)
LL17484	2155.0 (84.84)	2158.1 (84.96)
(LENGTH IN MM) (INCHES)		

