

ADVANCED ILLUMINATION LL174 LINEAR LIGHT

Expandable High Power Lighting

LL174-730C5

LL174 bar light, 6", IR 730, C5 connector

- Developed for large areas or Line scan applications
- Available in increments of 152 mm (6 inches) up to 1 219 mm (48 inches)



PRODUCT DESCRIPTION

The LL174 is a high intensity bar light with a large degree of customisation. Available in 16 wavelengths, expandable up to 84" in 6" increments.

There is optional heat sink for higher performance and/or high ambient temperature.

3 different lens options are also available, arrow, medium and wide beam spreads.

Power options include:

- C1 connector - for use with DCS series controllers
- C5 connector - for use with Pulsar 320 strobe controller
- Continuous in-line controller - powered by 24V power supply
- Combination strobe/continuous in-line controller - powered by 24V power supply
- Default-OFF strobe/continuous in-line controller - powered by 24V power supply
- Flying/tinned leads - powered by 24V power supply

All Wavelength options:

- UV - 365, 375, 385, 395
- Violet - 405
- Royal blue - 455
- Blue - 470
- Cyan - 505
- Green - 530
- Amber - 590
- Red orange - 625
- Red - 660
- Infrared - 730, 850, 940
- White - WHI

For enquiries or quotes for sizes and power options not listed here please [contact us](#).


TECHNICAL DATA

TECHNICAL DATA

Wavelength	730
Colour	Infrared
Length	174 mm

Width	34 mm
Connector/controller	C5 connector
Standard cable length	Up to 2 meters
Photobiological risk factor IEC 6247	Group 1 (low risk)
Operating temperature	0°C - 60°C
Approvals	IEC 62471, CE, RoHS
IP class	IP65
Weight	195.1 g

LL174		
ROD TYPE	NOV-RALED	RALED
LL174	173.7 (6.84)	176.8 (6.96)
LL17412	126.1 (12.84)	129.2 (12.96)
LL17418	178.6 (18.84)	181.7 (18.96)
LL17430	293.4 (30.84)	296.5 (30.96)
LL17436	355.4 (36.84)	358.5 (36.96)
LL17442	388.2 (40.84)	391.3 (40.96)
LL17448	420.2 (43.84)	423.3 (43.96)
LL17454	452.2 (46.84)	455.3 (46.96)
LL17460	484.2 (49.84)	487.3 (49.96)
LL17466	516.2 (52.84)	519.3 (52.96)
LL17472	548.2 (55.84)	551.3 (55.96)
LL17478	580.2 (58.84)	583.3 (58.96)
LL17484	612.2 (61.84)	615.3 (61.96)
(LENGTH IN MM) (INCHES)		



LL174		
ROD TYPE	NOV-RALED	RALED
LL174	173.7 (6.84)	176.8 (6.96)
LL17412	126.1 (12.84)	129.2 (12.96)
LL17418	178.6 (18.84)	181.7 (18.96)
LL17430	293.4 (30.84)	296.5 (30.96)
LL17436	355.4 (36.84)	358.5 (36.96)
LL17442	388.2 (40.84)	391.3 (40.96)
LL17448	420.2 (43.84)	423.3 (43.96)
LL17454	452.2 (46.84)	455.3 (46.96)
LL17460	484.2 (49.84)	487.3 (49.96)
LL17466	516.2 (52.84)	519.3 (52.96)
LL17472	548.2 (55.84)	551.3 (55.96)
LL17478	580.2 (58.84)	583.3 (58.96)
LL17484	612.2 (61.84)	615.3 (61.96)
(LENGTH IN MM) (INCHES)		

