OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

ADVANCED ILLUMINATION AL143 AREA LIGHTING

2x3 spot light

AL143-36524
Ai General Purpose Spot Light, UV 365, 24V



- Bright area lighting for long distances or large work areas
- Compact design - only 28 mm high
- M6 nut ducts for easy installation

PRODUCT DESCRIPTION

The AL143 spot/bar light is in a 2x3 design, available in a wide range of wavelengths and multiple lens options. It is the ideal illumination for medium working distances, with convenient mounting with an M4 nut channel.

Power options include:

- C1 connector - for use with DCS series controllers
- C5 connector - for use with Pulsar 320 strobe controller
- Continuous in-line controller - powered by 24V power supply
- Combination strobe/continuous in-line controller - powered by 24V power supply
- Default-OFF strobe/continuous in-line controller - powered by 24V power supply
- Flying/tinned leads - powered by 24V power supply

Other Wavelength options:

- UV - 365, 375, 385, 395, 405
- Royal blue - 455
- Blue - 470
- Cyan - 505
- Green - 530
- Amber - 590
- Red orange - 625
- Infrared - 730, 850, 940
- White - WHI

For enquiries or quotes for wavelength and power options not listed here please contact us.

TECHNICAL DATA

TECHNICAL DATA

Wavelength	365
Colour	Ultraviolet
Length	92.1 mm
Connector/controller	Flying/tinned leads
Standard cable length	Up to 2 meters
Photobiological risk factor IEC 6247	Group 2 (moderate risk)
Operating temperature	0 - 60°C
Approvals	IEC 62471, CE, RoHS

IP class	IP65
Weight	140.6 g

