

## ADVANCED ILLUMINATION AL143 AREA LIGHTING

2x3 spot light

AL143-625I3

Ai General Purpose Spot Light, red orange 625, I3

- Bright area lighting for long distances or large work areas
- Compact design - only 28 mm high
- M6 nut ducts for easy installation



### PRODUCT DESCRIPTION

The AL143 spot/bar light is in a 2x3 design, available in a wide range of wavelengths and multiple lens options. It is the ideal illumination for medium working distances, with convenient mounting with an M4 nut channel.

Power options include:

- C1 connector - for use with DCS series controllers
- C5 connector - for use with Pulsar 320 strobe controller
- Continuous in-line controller - powered by 24V power supply
- Combination strobe/continuous in-line controller - powered by 24V power supply
- Default-OFF strobe/continuous in-line controller - powered by 24V power supply
- Flying/tinned leads - powered by 24V power supply

Other Wavelength options:

- UV - 365, 375, 385, 395, 405
- Royal blue - 455
- Blue - 470
- Cyan - 505
- Green - 530
- Amber - 590
- Red orange - 625
- Infrared - 730, 850, 940
- White - WHI

For enquiries or quotes for wavelength and power options not listed here please [contact us](#).

## TECHNICAL DATA

### TECHNICAL DATA

Wavelength	625
Colour	Red orange
Length	92.1 mm
Connector/controller	Strobe/continuous in-line controller
Standard cable length	Up to 2 meters
Photobiological risk factor IEC 6247	Group 1 (low risk)

<b>Operating temperature</b>	0 - 60°C
<b>Approvals</b>	IEC 62471, CE, RoHS
<b>IP class</b>	IP65
<b>Weight</b>	140.6 g

