

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

ADVANCED ILLUMINATION AL143 AREA LIGHTING

2x3 spot light

AL143-530I3

Ai General Purpose Spot Light, green 530, I3





- Bright area lighting for long distances or large work areas
- Compact design only 28 mm high
- M6 nut ducts for easy installation

PRODUCT DESCRIPTION

The AL143 spot/bar light is in a 2x3 design, available in a wide range of wavelengths and multiple lens options. It is the ideal illumination for medium working distances, with convenient mounting with an M4 nut channel.

Power options include:

- C1 connector for use with DCS series controllers
- C5 connector for use with Pulsar 320 strobe controller
- Continuous in-line controller powered by 24V power supply
- Combination strobe/continuous in-line controller powered by 24V power supply
- Default-OFF strobe/continuous in-line controller powered by 24V power supply
- Flying/tinned leads powered by 24V power supply

Other Wavelength options:

- UV 365, 375, 385, 395, 405
- Royal blue 455
- Blue 470
- Cyan 505
- Green 530
- Amber 590
- Red orange 625
- Infrared 730, 850, 940
- White WHI

For enquiries or quotes for wavelength and power options not listed here please contact us.

TECHNICAL DATA

TECHNICAL DATA

| Wavelength | 530 |
|--------------------------------------|--------------------------------------|
| Colour | Green |
| Length | 92.1 mm |
| Connector/controller | Strobe/continuous in-line controller |
| Standard cable length | Up to 2 meters |
| Photobiological risk factor IEC 6247 | Group 1 (low risk) |

| Operating temperature | 0 - 60°C |
|-----------------------|---------------------|
| Approvals | IEC 62471, CE, RoHS |
| IP class | IP65 |
| Weight | 140.6 g |

