OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

ADVANCED ILLUMINATION AL150 BALA BAR LIGHT

Broad Area Linear Array

AL150006-660I3
BALA bar light, 6 LEDs, red 660, strobe/continuous controller



- Designed to handle a long, wide field with low angle of view
- Available in 25 mm (1 ") increments up to 80"

PRODUCT DESCRIPTION

Designed for applications that require broad illumination over a wide area, or for applications requiring an even broader field of illumintion, utilise 2 BALA bar lights in parallel.
The AL150 bar light series is expandable in 1" increments up to 82".

Power options include:

- C1 connector - for use with DCS series controllers
- C5 connector - for use with Pulsar 320 strobe controller
- Continuous in-line controller - powered by 24V power supply
- Combination strobe/continuous in-line controller - powered by 24V power supply
- Default-OFF strobe/continuous in-line controller - powered by 24V power supply
- Flying/tinned leads - powered by 24V power supply

Other Wavelength options:

- UV - 395
- Blue - 470
- Green - 520
- Red - 625, 660
- Infrared - 880
- White - WHI

For enquiries or quotes for sizes and power options not listed here please contact us.

TECHNICAL DATA

TECHNICAL DATA

Wavelength	660
Colour	Red
Length	41 mm
Width	34 mm
Connector/controller	Strobe/continuous in-line controller
Standard cable length	Up to 2 meters
Photobiological risk factor IEC 6247	Group 1 (low risk)
Operating temperature	0°C - 60°C

Approvals	IEC 62471, CE, RoHS
IP class	IP50

Number of LEDs	6

