

## BASLER CAMERA BACK LIGHTS

120x120mm, 60x60mm

2200000648

Back light, 63x90x15(60x60), 635 Red



- Integrated controller for perfect synchronisation
- Blue, red or white LEDs
- 120 x 120mm or 60 x 60mm light emitting surface
- Easy access to strobing and over drive functions

### PRODUCT DESCRIPTION

Basler's back lights are high-performance LED illumination solutions designed to enhance image contrast and edge detection in machine vision systems. Available in various sizes—from compact 60 × 60 mm models to larger 200 × 300 mm panels—they offer LED colour options including red, white, blue, and infrared. These back lights feature integrated or external controllers, support strobe and continuous operation modes, and are compatible with Basler's SLP (Smart Light Profile) technology for seamless synchronisation with Basler cameras. For instance, the Basler Standard Light Back-200x300 series provides a luminous area of 200 × 300 mm, operates at 24 VDC, and delivers up to 43 klux illuminance at 0 mm distance, making it suitable for applications requiring high-intensity backlighting.

In practical applications, Basler back lights are ideal for tasks that require precise silhouette imaging, such as dimensioning, foreign object detection, and fill level measurement. By placing the back light behind the object and aligning it with the camera, the system captures high-contrast images that clearly define object contours. This setup is particularly effective in quality control processes within manufacturing, packaging, and food inspection industries, where accurate edge detection is crucial for identifying defects or inconsistencies.

## TECHNICAL DATA

### TECHNICAL DATA

<b>Wavelength</b>	635
<b>Colour</b>	Red
<b>Light dimensions</b>	60mm x 60mm
<b>Length</b>	63 mm
<b>Width</b>	90 mm
<b>Height</b>	15 mm
<b>Connector/controller</b>	Integrated controller, constant voltage (66.2x30x20mm)
<b>Input voltage</b>	24 V DC (±10%)
<b>Power consumption</b>	6.1 W
<b>Operating temperature</b>	0 ... 40°C
<b>Storage temperature</b>	-20 ... +60°C
<b>Operating humidity</b>	20-85%
<b>Humidity storage</b>	20-85%
<b>Approvals</b>	CE, EN61000-6-2, EN61000-6-4, RoHS

Weight

130 g

