

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

## **ADVANCED ILLUMINATION CX SERIES BACK LIGHTS**

• 30% brighter than same size surface mount light · Uniform illumination and low heat output • Available in 1" x 1" increments up to 16" x 16".

Expandable Side Lit Collimated

CX0404-WHIIC





## PRODUCT DESCRIPTION

The CX series of backlights are expandable, available in 1" increments up to 16" X 16".

Edge-lit collimated backlights are characterized by their high intensity and low heat output. These collimated backlights produce a distinct silhouette and can improve edge detection of curved objects.

Power options include:

- C1 connector for use with DCS series controllers
- C5 connector for use with Pulsar 320 strobe controller
- Continuous in-line controller powered by 24V power supply
- Combination strobe/continuous in-line controller powered by 24V power supply
- Default-OFF strobe/continuous in-line controller powered by 24V power supply

For enquiries or quotes for sizes and power options not listed here please contact us.

## **TECHNICAL DATA**

## **TECHNICAL DATA**

Wavelength	WHI
Colour	White
Width	101.6 mm
Connector/controller	Continuous in-line controller
Standard cable length	Up to 2 metres
Photobiological risk factor IEC 6247	Group 1 (low risk)
Operating temperature	0°C - 60°C
Approvals	IEC 62471, CE, RoHS
IP class	IP50
Weight	561.6 g

