

OEM Automatic Ltd

Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

ADVANCED ILLUMINATION AL295 MICROBRITE BAR LIGHT

Compact Area Lighting

AL295-150-455C5 Ai MicroBrite™ Bar Light, 150mm, Royal Blue, Pulsar





PRODUCT DESCRIPTION

The AL295 is part of the Microbrite family of high performance, compact machine vision lights. Outperforming the competition with a high intensity output of 73 kLux at a working distance of 100mm. The AL295 is available is expandable sizes in 3" increments up to 18".

Power options include:

- C1 connector for use with DCS series controllers
- C5 connector for use with Pulsar 320 strobe controller
- Continuous in-line controller powered by 24V power supply
- Combination strobe/continuous in-line controller powered by 24V power supply
- Default-OFF strobe/continuous in-line controller powered by 24V power supply
- Flying/tinned leads powered by 24V power supply

Other Wavelength options:

- UV 365, 375, 385, 395, 405
- Royal blue 455
- Blue 470
- Cyan 505
- Green 530
- Amber 590
- Red orange 625
- Red 660
- Infrared 730, 850, 940
- White WHI

For enquiries or quotes for wavelength and power options not listed here please contact us.

TECHNICAL DATA

TECHNICAL DATA

| Wavelength | 455 |
|------------|------------|
| Colour | Royal blue |
| Length | 166 mm |

| Width | 20 mm |
|--------------------------------------|-------------------------|
| Connector/controller | C5 connector |
| Standard cable length | Up to 2 meters |
| Photobiological risk factor IEC 6247 | Group 2 (moderate risk) |
| Operating temperature | 0 - 60°C |
| Approvals | IEC 62471, CE, RoHS |
| IP class | IP50 |
| Weight | 68.9 g |

